



DECLARATION OF PERFORMANCE

N°: 1 271

1. Product type and identification

Fasatyl eco Fix – EPDM waterproofing membrane (0.6 mm thick)

2. Name and contact address of the manufacturer

BOSIG GmbH
Brunnenstrasse 75-77
73333 Gingen / Fils
Germany

3. Intended use

EN 13984: Vapour control layer (Type A)

4. System of assessment and verification of constancy of performance (AVCP)

3

5. Notified body

Testing carried out at 0370

6. Declared performance

| Essential characteristics | Performance | Test standard | Harmonised technical specification |
|---------------------------|-------------|-----------------|------------------------------------|
| Reaction to fire | E | EN 13501-1 | EN 13984:2013 |
| Watertightness (2 kPa) | Pass | EN 1928 | |
| Water vapour permeability | 160.000 | EN 1931 | |
| Impact resistance | NPD | EN 12691 | |
| Joint shear resistance | NPD | EN 12316-2 | |
| Tensile strength | ≥ 6 MPa | EN 12311-2 | |
| Elongation | ≥ 250 % | EN 12311-2 | |
| Tear resistance | ≥ 10 N | EN 12310-2 | |
| Durability against ageing | Pass | EN 1296/EN 1931 | |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 2.

Signed for and on behalf of the manufacturer by:

Name and Title

Dr. Christian Hermann, Quality Manager

Gingen, June 17, 2014

i. A.

