



Fasatop FH Standard

N°: 1 296

1. Product classification code:

Flexible sheets for waterproofing for application as underlays for walls

2. Identification number of the product:

Fasatop FH Standard

Batch number: See product packaging / labeling

3. Intended use

Underlays for walls

4. Manufacturer

BOSIG GmbH Brunnenstrasse 75-77 73333 Gingen / Fils Germany

5. Authorized representative

Not relevant

6. System of assessment and verification:

System 1 and System 3

7. Notified body:

MPA Braunschweig Identification no.: 0761

Testing of fire behaviour, issuing of the certificate of constancy of performance no. 0761-CPR-1038

KIWA TBU Greven Identification no.: 0799

Testing of resistance against water penetration and of water vapour permeability and determination of product

type

8. Declared performance

Essential characteristics	Performance			Harmonised
	Desired value	Tolerance		Standard
		Min.	Max.	Standard
Length [m]	50	- 0 %		
Width [mm]	50 to 1500	DIN 7715-5: 1979-11, class P3		
Straightness [mm per 10 m]	< 30			
Fire behaviour	B-s1, d0			
Resistance against water penetration	W1			
Resistance against water penetration	W1			
after ageing				EN 13859-2: 2010
Surface weight [g/m²]	195	- 10 %	+ 10 %	
Water vapour permeability s _d [m]	0.13	- 0.03	+ 0.03	
Maximum tensile force length- / crosswise [N/5cm]	340 / 240	- 30	+ 30	
Maximum tensile force length- / crosswise [N/5cm] after ageing	320 / 220	- 30	+ 30	
Extension at max. tensile force length- / crosswise [%]	50 / 70	- 15	+ 15	
Extension at max. tensile force length- / crosswise [%] after ageing	40 / 60	- 15	+ 15	
tear propagation resistance (nail shaft) length- / crosswise [N]	210 / 300	- 30	+ 30	
Cold bending behaviour [°C]	< - 20			

9. The performance of the product identified in point 1. and point 2. is in conformity with the declared performance in point 8. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and Title

Dr. Christian Hermann, Quality Manager

i. A. frilidingfruum

Gingen, November 8, 2021

DoP_Fasatop FH Standard_1296_Vers 2.0-e