

### Processing notes for self-adhesive foam tapes:

- The surfaces on which the tapes have to be adhered to have to be clean, dry and free from grease and oil as well as free of ice and frost.
- Never let the tapes run around corners.
- Please pay attention that no air bubbles are caught between the adhesive layer and the material surface.
- Please avoid overlapping.
- The tapes have to be stored at a moderate temperature.
- The self-adhesive coating attains maximum adhesion at approximately + 20 °C.
- The minimum processing temperature is + 5° C.
- Please also observe our technical data sheet!

### Attention! Important Note:

Above information are based on best present knowledge of current technology, but do not guarantee faultless processing of our products. The information is based on practical results of our tests, but is not binding and does not constitute warranties of characteristics in terms of Federal Supreme Court jurisdiction. Our information does not constitute a legally binding assurance of certain properties or suitability for a specific purpose. Supplementary information by our specialists are merely recommendations, for which no liability is accepted.

Due to the many possible applications of our products, we recommend subjecting the project to a thorough suitability test on original materials before release for further application.

Since our information are non-binding we do not warranty their correctness. For this reason we accept no liability for possible improper processing based on information submitted by our employees.

These processing notes replace all previous versions and are valid until a new version is issued, or until Dec. 31, 2020. Please request the latest version after Jan 01, 2021.

Dr. Hermann, Anwendungstechnik / Application Technology, Gingen / Fils